

01-966

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR PATENT

ON

DUAL PURPOSE PCI-X DDR CONFIGURABLE TERMINATOR/DRIVER

BY

Frank Gasparik
17235 Fairplay Drive
Monument, CO 80132
Citizen of United States

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" Mailing Label Number: EV 013 245 041 US

Date of Deposit: December 20, 2001

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231

BY:


ReNea D. Berggren

*DUAL PURPOSE PCI-X DDR CONFIGURABLE TERMINATOR/DRIVER*FIELD OF THE INVENTION

[0001] The present invention generally relates to the field of Peripheral Component Interfaces (PCI) utilized in computer systems and the like, and particularly to a dual purpose PCI-X DDR configurable terminator/driver providing programmable termination of the interface.

BACKGROUND OF THE INVENTION

[0002] The Peripheral Component Interface (PCI) is used in personal computers as an interface between the central processing unit (CPU) and various peripheral components such as VGA controllers, and the like. The PCI-X 2.0 DDR provides PCI technology with Double Data Rate (DDR) transfers. The original PCI bus was an unterminated transmission media mostly used in the point-to-point connections. This methodology worked well as long as the board trace length was restricted and the clock/data rates were below 100MHz (legacy PCI systems have data rates equal to 33MHz and 66MHz). The signal integrity deteriorates rapidly in data transmission systems utilizing the unterminated transmission lines. The mismatch between the transmission line characteristic impedance and the load impedance (in this case the load impedance is an open circuit) will cause the signal reflections and negatively affect the signal integrity.

[0003] Future generations of PCI, such as PCI-X DDR, will increase the data rates to frequencies (f) of 133 MHz and beyond. Shorter signal periods ($T=1/f$) will not allow sufficient time for the signal overshoot/undershoot and ringing to settle out. Even with short transmission lines (board traces) the reflections must be minimized and controlled by proper line termination. Use of external line termination is unacceptable for a number of reasons. First, external termination is costly, incurring additional component, assembly labor and board area costs. Further, signal integrity is degraded due to the

added external devices and trace parasitics. Moreover, the terminator must be made switchable, i.e. must be turned off, when the direction of data transfer is reversed.

[0004] The addition of an on-chip terminator costs an unacceptable silicon area penalty. The PCI-X DDR transceivers are located on the silicon chip periphery, called pads. The PCI-X DDR driver consumes the largest portion of the pad due to large MOSFET output devices. The addition of another large MOSFET device for implementation of the discrete terminator will consume a large amount of additional pad silicon area and will increase the PCI pad parasitic capacitance which is harmful to the signal integrity.

[0005] FIG. 1 illustrates a typical PCI-X system 100. As shown in FIG. 1, data transfer is from the PCI₁ block 102 to the PCI₂ block 104. The driver DX₁ 106 is enabled to drive the transmission line X₁ 108 such as PC board trace. The transmission line X₁ 108 far-end terminal X_{1out} 110 is connected to the input of the enabled receiver RX₂ 112. The receiver RX₁ 114 and the driver DX₂ 116 are disabled during this data transmission.

[0006] For high signal integrity, it is desirable to have the driver DX₁ 106 output impedance Z_{out} equal to the transmission line characteristic impedance Z_o , i.e. $Z_{out} = Z_o$. Thus, it is desirable to have the input impedance Z_{in} of the receiver RX₂ 112 also equal to the transmission line characteristic impedance Z_o , i.e. $Z_{IN} = Z_o$. In the embodiment shown in FIG. 1, the input impedance Z_{IN} of receiver RX₂ 116 is many orders of magnitude higher than the characteristic impedance Z_o of the transmission line, i.e. $Z_{IN} \gg Z_o$. In existing PCI systems no termination is used at the far end of the transmission line. This results in impedance mismatch for the unterminated transmission line. Consequently, signal reflections will cause severe distortions to the signal and negatively affect the reliability of data transmission.

[0007] During the mode of transmission described, the far end driver DX₂ 116 is tri-stated, idle, while the receiver RX₂ 112 is receiving the incoming data stream. The present invention employs the unused driver DX₂ devices 116 for the purpose of implementation of proper far end transmission line termination.

SUMMARY OF THE INVENTION

[0008] Accordingly, the present invention is directed to a dual purpose PCI-X DDR configurable terminator/driver suitable for use in a PCI-X DDR system for providing programmable termination of the interface in a PCI-X system. In exemplary embodiments, the PCI-X DDR configurable terminator/driver includes a plurality of N-channel devices divided into at least two groups and a plurality of P-channel also divided into at least two groups. A driver control individually controls selected ones of the groups of N-channel and P-channel devices on or off for providing internal termination to the transmission line. The configurable PCI-X DDR driver/terminator is configurable in three termination modes: pull-up mode, pull-down mode, and symmetric mode.

[0009] The configurable PCI-X DDR driver/terminator may utilize existing driver devices without the additional chip area penalty, and may be programmable for correct terminator impedance value $R_T = Z_0$ and maintains the process/voltage/temperature characteristics of the termination impedance. Preferably, the configurable PCI-X DDR driver/terminator does not increase the parasitic capacitance of the pad by using the same devices of the driver. The driver/terminator may further have applications in other transmission methodologies such as AGP4X, AGP8X, and the like.

[0010] It is to be understood that both the forgoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention as claimed. The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate an embodiment of the invention and together with the general description, serve to explain the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The numerous advantages of the present invention may be better understood by those skilled in the art by reference to the accompanying figures in which:

FIG. 1 is a block diagram illustrating an exemplary PCI-X system;

FIG. 2 is a block diagram illustrating a PCI-X DDR system with pull-up type termination in accordance with an exemplary embodiment of the present invention; and

FIG. 3 is a circuit diagram illustrating a configurable PCI-X DDR Driver providing an internal terminator in accordance with an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Reference will now be made in detail to the presently preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

[0013] FIG. 2 illustrates a PCI-X DDR system 200 in accordance with an exemplary embodiment of the present invention. Like the PCI-X system 100 shown in FIG. 1, data transfer is again from the PCI₁ block 202 to the PCI₂ block 204. The driver DX₁ 206 is enabled to drive the transmission line X₁ 208 such as a PC board trace. The transmission line X₁ 208 far end terminal X_{1out} 210 is connected to the input of the enabled receiver RX₂ 212 and to the terminal T₁ 214. The receiver RX₁ 216 and the driver DX₂ 218 are both disabled during this data transmission.

[0014] In exemplary embodiments of the present invention, correct impedance matching is obtained among the driver, transmission line and receiver input. The output impedance Z_{OUT} of driver DX₁ 206 is matched to the transmission line characteristic impedance Z_o. The far end transmission line becomes properly terminated by making the terminator T₁ resistance R_T = Z_o. Thus, the receiver RX₂ high input impedance Z_{IN} becomes inconsequential, resulting in an impedance match for the entire PCI-X DDR system 200. As a result, signal reflections are substantially minimized and signal integrity is substantially improved, increasing the reliability of data transmission.

[0015] Referring now to FIG. 3, a simplified PCI-X DDR driver/terminator 300 in accordance with an exemplary embodiment of the present invention is described. The PCI-X DDR driver 300 (which corresponds, for example, to driver DX₂ 218 shown in FIG. 2) includes a driver control 302. Preferably, the driver control 302 includes the

impedance controller to correct for process/voltage/temperature (PVT) effects. In FIG. 3, the devices MP_{1x} , MP_{2x} , ... MP_{ix} 304-308 and MN_{1x} , MN_{2x} , ... MN_{ix} 310-314 represent groups of devices even though only one device is shown for simplicity. In exemplary embodiments, the sizes of these devices are weighted to achieve the desired output impedance in conjunction with discrete resistors R_{Pi} 316 or R_{Ni} 318 for the given PVT conditions.

[0016] As shown in FIG. 3, the PCI-X DDR driver 300 is subdivided into groups of P and N channel devices 320 & 322 along dashed lines 324 & 326. Each group 320 & 322 is individually controlled by driver control 302 to be either on or off. This approach permits selection of any of the device groups 320 or 322 independently allowing the driver 300 to be configured to provide three different termination types: pull-up type, pull-down type, and symmetric type. For a pull-up type termination, the terminator impedance ($R_T = Z_0$) from transmission line end X_{Iout} 210 (FIG. 2) is connected to the power supply VDD. The power supply VDD acts as an AC ground. For a pull-down type termination, the terminator impedance ($R_T = Z_0$) from transmission line end X_{Iout} 210 (FIG. 2) is connected to the system ground VSS. Finally, for a symmetric type termination, the terminator impedance ($R_T = Z_0$) from transmission line end X_{Iout} 210 (FIG. 2) is connected to both VDD (R_P) and VSS (R_N). In this case the equivalent load impedance is equal to the parallel combination of these two resistors, i.e. $R_T = R_P \parallel R_N$.

[0017] The implementation of a pull-up type PCI-X DDR terminator for a specific impedance value is now described for illustration. All groups of N channel devices are tri-stated by setting the V_{N1} , V_{N2} , ... V_{Ni} control terminals 328-332 low via driver control 302. To select the particular value of terminal impedance R_T , selected V_{P1} , V_{P2} , ... V_{Pi} control terminals 334-338 are also set low by the driver control 302. For example, to obtain a value of $R_T = 50\Omega$, the V_{P1} , V_{P5} , ... V_{P7} control terminals may be set low, enabling only selected groups of corresponding MP_{1x} , MP_{5x} , and MP_{7x} devices.

[0018] For implementation of a pull-down type of termination, the groups of N-channel devices are enabled by setting the V_{N1} , V_{N2} , ... V_{Ni} control terminals 328-332 high via

the driver control 302. All P-channel devices are disabled for the pull-down type of terminator.

[0019] For implementation of a symmetric type of termination, selected groups of both P and N-channel devices are enabled to meet the overall termination impedance $R_T = R_P \parallel R_N$ as depicted in FIG 3.

[0020] The PCI-X DDR driver 300 may utilize existing driver devices without the additional chip area penalty, and may be programmable for correct terminator impedance value $R_T = Z_o$ and maintains the process/voltage/temperature characteristics of the termination impedance. Preferably, the driver 300 does not increase the parasitic capacitance of the pad by using the same devices of the driver. The driver/terminator may further have applications in other transmission methodologies such as AGP4X, AGP8X, and the like.

[0021] It is believed that the dual purpose PCI-X DDR configurable terminator/driver of the present invention and many of its attendant advantages will be understood by the forgoing description. It is also believed that it will be apparent that various changes may be made in the form, construction and arrangement of the components thereof without departing from the scope and spirit of the invention or without sacrificing all of its material advantages. The form herein before described being merely an explanatory embodiment thereof. It is the intention of the following claims to encompass and include such changes.